



## P6.6 Outdoor Die-Casting Magnesium Light Weight Rental LED Display

<b>Model</b>		<b>P6.6-OR6S-SMD3535-48x24-L960H960</b>			
<b>1. LED</b>					
					
Color	Package	Intensity	Viewing angle	Wavelength	Testing condition
Red	SMD3535	750mcd	120	620nm	25°C, 20mA
Green	SMD3535	2100mcd	120	520nm	25°C, 20mA
Blue	SMD3535	530mcd	120	470nm	25°C, 20mA

<b>2. LED Module</b>	
	
Pixel Pitch	6.6
Pixel configuration	SMD3535
Density	22,497pixels/m <sup>2</sup> (real pixel)
Module Resolution	48(L) * 24(H)
Module Dimension	320(L) * 160(H) * 13(D)
Driving Mode	Constant current, 1/6 duty
Module Mask	Pure black mask---high contrast screen

<b>3. LED Cabinet</b>	



960x960mm Die-Casting Magnesium Cabinet

Module Quantity in a Cabinet	3(L) * 6(H)
Cabinet Dimension	960(L) * 960(H) * 85(D)mm
Cabinet Resolution	144(L) * 144(H)
Cabinet Material	Die-Casting Magnesium
Cabinet Weight	≈20KG

#### 4. Electricity Parameter

##### Optical Ratings

Brightness	≥5200 cd/m <sup>2</sup>
Viewing Angle	120°(Horizontal); 120°(Vertical)
Best Viewing Distance	≥6.5m
Gray Grade	8096 levels for each color
Display Color	530,654,068,736 color
Brightness Adjustment	100 grades by software or automatically by sensor

##### Power Supply

Operation Power	AC100-240V 50-60Hz    Switchable
Max. Power Consumption	780 W/m <sup>2</sup>
Average Power Consumption	≈250 W/m <sup>2</sup>

##### Control System

Correction Scale Level	13bits
Frame Frequency	≥60Hz
Screen Refresh Frequency	≥1920Hz
Gamma Correction	-5.0~5.0
Input Signal	Composite Video, S-video, DVI, HDMI, SDI, HD-SDI
Control Distance	100m(Ethernet cable);



# SHENZHEN EAGER LED CO., LTD.

LED Display Factory    Web: [www.eagerled.com](http://www.eagerled.com)

	20KM(optical fiber cable)
Support VGA Mode	800*600, 1024*768, 1280*1024, 1600*1200
Color Temperature	5000—9300 adjustable
Brightness Correction	Pixel by pixel, module by module, cabinet by cabinet
<b>Reliability</b>	
Working Temperature	-20~+60 °C
Stored Temperature	-30~+70 °C
Working Humidity	10%~90% RH
Lifetime	100,000 hours
MTBF	5000 hours
Continuous Working Time	≥72 hours
Protection Grade	IP65
Out of Control Pixel Rate	≤0.01%