

P4 Outdoor SMD HD LED Display Panel

Pictures of P4 Outdoor SMD HD LED Display Module:



Technical Parameters of P4 Outdoor SMD HD LED Display Module:

Item	Parameter	Remark
LED type	SMD2022	
Pixel configuration	1R1G1B	
Module size	320*320 mm	
Module resolution	80*80 pixels	
Module weight	1.2 kg	
Working voltage	DC4.2V	
Module Power	62W	
Driving IC	MBI5124	
Driving way	1/10 duty	
Working temperature	-20°C - +60°C	
HUB card	HUB44	

Pictures of P4 Outdoor SMD HD LED Display Die-casting Aluminum Cabinet:





SHENZHEN EAGER LED CO., LTD.

LED Display Factory Web: www.eagerled.com

Parameters of P4 Outdoor SMD HD LED Display:

Item	Parameter	Remark
Pixel Pitch	4 mm	
Cabinet Material	Die-cast aluminum	
Color	Gray	
Cabinet Dimension	640*640*105 mm	
Cabinet Resolution	160*160 pixels	
Module quantity	2*2	
Density	62,500pixels/m ²	
White balance brightness	≥5500CD/m ²	
Color temperature	6500K—8000K	
Viewing angle	H:120;V:120	
Protection grade	Front/Rear:IP65/IP65	
Non-Flatness	<0.5mm	
Module interval	<0.5mm	
Cabinet Weight	14kg/Cabinet	With power supply
Packaging Gross	100kg(Estimated data)	4pcs / Case
Packaging dimension	780*780*940mm	4pcs / Case
Maximal power/m ²	750W/m ²	
Average power/m ²	250W/m ²	
Frame frequency	≥60Hz	
Refresh frequency	1920Hz	Depending on the selected driver chip and control system
Gray grade	14bit	
Brightness adjusted	256 grade by auto-optic/color &8 grade by	
Input signal	RF,S-video,RGB,RGBHV,YUV,YC&Composition,etc	
Control system	Novastar / Linsn / Colorlight	
System supports	Windows XP,WIN 7	
MTBF	>5000h	
Life-span	>100000h	
Speckles rate	<0.0002	

Package:



P4 Outdoor SMD HD LED Display System Diagram

